



COMPACT VARIABLE DATA PRINTER



Kolkata Office : H2-95, Ho Chi Min Sarani, Sarsuna, Kolkata - 700061, W.B. - INDIA

Faridabad Office : Plot no. 20, Sector - 87, faridabad - 121002
(Near Shraddha Mandir School)

Ghaziabad Works : 150, KAD KAD MAIDAN, CHIKAMBARPUR, U.P. BORDER,
SAHIBABAD, Ghaziabad, Uttar Pradesh 201006, India

Call : (+91) 9073950891 / 7290033620 / 033 2452 1065

Email : sales@btprintopkg.com

www.btprintopkg.com

***1040 THERMAL INKJET PRINTER**



TECHNICAL SPECIFICATIONS

Plug and print with HP TIJ.25
Dimensions (LxWxH): 107.5 x 74.5 x 83 mm / 4.23 x 2.93 x 3.27 inches
Weight: 450g (excluding cartridge)
Display: Automatic rotation 2.8"256K colors TFT LCD display
Power Supply: AC 100V–240V, 50/60Hz, 1.4A. Maximum power consumption: 48W

Anti-shock mounting mechanism for printer protection
Stronger and smaller skid plate design
Throw Distance: up to 6mm

STANDARD FEATURES

Bluetooth connection via smart phones and tablets using Android devices
Stand-alone operation with Wireless keyboard direct connection
Free template design and control with PC application
AUX I/O port for external sensor, encoder and alarm kit connection
Flash USB2.0 for firmware, font and logo loading
Built-in and adjustable photo sensor
Automatic data back-up system
Nozzle switching and self-cleaning capabilities to extend cartridge lifetime
Store up to 100 messages in printer's memory
Password protection
Automatic recognition of inks (aqueous or solvent) and application of appropriate printing parameters
User-friendly cartridge slot design
Hot-swap: Circuit protection for quick cartridge changeover
Real time report to Android devices

PRINTABILITY AND SPEEDS

Menu languages: English (default), Finnish, Spanish, German, French, Russian, Vietnamese, Chinese, Korean, Portuguese, Polish, Dutch, Italian, Turkish, Czech and Indonesia
Printable characters: Windows true fonts (with PC) and multi-languages with smart devices
Message line with predictable data: up to 6 lines from 1.69 – 12.7mm
Maximum characters input up to 150 per line
Maximum length of template up to 500mm
Printability: Alphanumeric, logos, date/time, expiry date, Julian date, shift code, counter/lot box code, multiple types of variable barcodes and database
Resolutions: Max 600x600dpi
Print speed: Max 76m/min @ 300x300dpi
Up to 5 levels of optical density

Solvent based ink for multi surface printing

INK SOLUTIONS AND ACCESSORIES

Water based general-purpose ink for printing on porous material
Support various colors of ink: Black, Red, Green, Blue, White,...

OPERATING TEMPERATURE AND WARRANTY

Operating temperature between 5°C and 50°C
12-month limited warranty